


Item no.: 2060-403/998-404
 Product description: 2 POLE PIN SPACING 4 MM / 0.157 IN



Produkt kann von Bild abweichen / product may differ

RoHS compliant

| | |
|--------------------------|------------------------|
| Product group | 3 (Multi Conn. System) |
| Color | light gray |
| No. of connection Points | 3 |
| No. of potentials | 3 |
| pole count | 3 |
| Height | 4.5 mm |
| Height | 0.177 in |
| Width | 11.9 mm |
| Width | 0.469 in |
| Depth | 13.1 mm |
| Depth | 0.516 in |
| Pin spacing from | 4 mm |
| Pin spacing from | 0.157 in |
| Pollution degree | 2 |
| Measured voltage EN | 160 V |
| Measured shock voltage | 2.5 kV |
| Current intensity EN | 9 A |
| Pollution degree | 2 |
| Measured voltage EN | 320 V |

Measured shock voltage
Current intensity EN
Connection method

2.5 kV
9 A
CAGE CLAMP®S Connection



| | |
|----------------------------------|----------------------------|
| Cross section [mm ²] | 0.2 - 0.75 mm ² |
| Wiring method | solid |
| Cross section [mm ²] | 0.2 - 0.75 mm ² |
| Cross section [AWG] | 24 - 18 AWG |
| Strip length from | 6 mm |
| Strip length to | 7 mm |
| Material group | I |

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected