

---

Item no.: 224-101  
Product description: LIGHTING CONNECTOR; STANDARD TYPE; CONTINUOUS SERVICE TEMPERATURE 105°C; CAGE CLAMP® CONNECTION

---



Packing unit 1000 10\*100 pieces

Cross section from [mm <sup>2</sup> ]	1 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	2.5 mm <sup>2</sup>
Cross section from [AWG]	14 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP® CONNECTION
Voltage CSA	300 V
Voltage UL	300 V
Current rating UL	20 A
Cross section from [mm <sup>2</sup> ]	0.5 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	2.5 mm <sup>2</sup>
Cross section from [AWG]	20 AWG
Cross section to [AWG]	16 AWG
Measured voltage EN	400 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	24 A
Weight	2.033 g
Color	gray
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	1
Height	15.5 mm



Width	8.5 mm
Width	0.335 in
Depth	20.5 mm
Depth	0.807 in
Strip length from	9 mm
Strip length to	11 mm
Strip length	0.39 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
224-101	ABS	04-HG476172-PDA	400	24	0,5-2,5
224-101	ASTA	Cert.No.174	400	24	0,5-2,5
224-101	BV	11914/AO	300	24	2,5
224-101	CSA	154112-1059435	300		14-12
224-101	DEMKO	119688/01/02			2,5
224-101	Dep.MaE	CS4574N	300	26	1x(0,5-2,5)
224-101	DNV	E7569	400	24	0,5-2,5
224-101	FIMKO	163400-01			2,5
224-101	KEMA	96.1739.01	400	24	2,5
224-101	LR	04/20013(E1)	400	24	2,5
224-101	NEMKO	P96191377			2,5
224-101	ÖVE	1193-032-01	400	24	0,5-2,5
224-101	RMR	11130002	400	24	0,5-2,5
224-101	RosTesT	B09523	400	24	0,5-2,5
224-101	SEMKO	9617079			2,5
224-101	UL	E69654	300	20	14-12
224-101	VDE	95667	400	24	2,5

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected