



PCB TERMINAL STRIP; 2 SOLDER PINS / POLE; 2 POLE; PIN SPACING 10/10.16 MM / 0.4 IN; FRONT-/SIDE-ENTRY; CAGE CLAMP® CONNECTION

Packing unit 200 4*50 pieces

Product group 4 (Printed Circuit)

Pin spacing from 10 mm

Pin spacing up to 10.16 mm

Pin spacing from 0.394 in

Pin spacing up to 0.4 in

pole count 2

Cross section from [mm²] 0.08 mm²

Cross section to [mm²] 2.5 mm²

Cross section from [AWG] 28 AWG

Cross section to [AWG] 12 AWG

Connection method CAGE CLAMP® CONNECTION

Measured voltage EN 500 V

Measured shock voltage 6 kV

Pollution degree 3

Current intensity EN 16 A

Measured voltage EN 1000 V

Measured shock voltage 6 kV

Pollution degree 2

Current intensity EN 16 A

Weight 2.63 g

Color gray

Wiring type Front-/Side-entry

No. of connection Points 1

No. of potentials 2

Height 13 mm

Height 0.512 in

Width 22.3 mm

Width 0.878 in

Depth 14 mm

Depth 0.551 in

Strip length from 5 mm

Strip length to 6 mm

Strip length 0.22 in