



1-CONDUCTOR PCB TERMINAL STRIP; 1 SOLDER PIN / POLE STAGGERED; 2 POLE;
PIN SPACING 2.5 MM / 0.098 IN; WITH PUSH BUTTONS; ANGLED TYPE-ENTRY

Packing unit 1 piece

Product group 4 (Printed Circuit)

Pin spacing from 2.5 mm

Pin spacing from 0.098 in

pole count 2

Cross section from [mm²] 0.2 mm²

Cross section to [mm²] 0.5 mm²

Cross section from [AWG] 24 AWG

Cross section to [AWG] 20 AWG

Wiring method f

Diameter from 0.4 mm

Cross section to [AWG] 20 AWG

Diameter to 0.8 mm

Cross section from [AWG] 26 AWG

Wiring method s (solid)

Connection method PUSH-WIRE CONNECTION

Measured voltage EN 250 V

Measured shock voltage 2.5 kV

Pollution degree 2

Current intensity EN 2 A

Weight 0.883 g

Color gray

Wiring type Angled Type

No. of connection Points 2

No. of potentials 2

Height 13.1 mm

Height 0.516 in

Width 6.5 mm

Width 0.256 in

Depth 12 mm

Depth 0.472 in

Strip length from 8.5 mm

Strip length to 9.5 mm

Strip length 0.35 in