
Item no.: 251-107
Product description: COMBI PCB TERMINAL BLOCK; AND IDC-CONTACT; 7
POLE; PIN SPACING 3.5 MM / 0.138 IN; PUSH-WIRE
CONNECTION



Packing unit 180 4*45 pieces

Pin spacing from	3.5 mm
Pin spacing from	0.138 in
pole count	7
Cross section from [mm ²]	0.5 mm ²
Cross section to [mm ²]	1.5 mm ²
Cross section from [AWG]	20 AWG
Cross section to [AWG]	16 AWG
Connection method	CAGE CLAMP® CONNECTION
Cross section from [mm ²]	0.5 mm ²
Cross section from [AWG]	20 AWG
Measured voltage EN	500 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	2 A
Weight	6.84 g
Color	white
Wiring type	Side-entry
No. of connection Points	14
No. of potentials	7
Height	19.2 mm
Height	0.756 in
Width	25.4 mm



Depth	13.2 mm
Depth	0.52 in
Strip length from	7.5 mm
Strip length to	8.5 mm
Strip length	0.31 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
251-107	CCA	DK2032	450	6	0,5-1,5
251-107	DEMKO	99-01851	450	6	0,5-1,5
251-107	RosTesT	B09523	450	6	0,5-1,5

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected