


Item no.: 254-154
 Product description: 2-CONDUCTOR PCB TERMINAL STRIP 2 SOLDER PINS /
 POLE 4 POLE PIN SPACING 5/5.08 MM / 0.2 IN



Produkt kann von Bild abweichen / product may differ

Packing unit 220 4*55 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Pin spacing from	5 mm
Pin spacing up to	5.08 mm
Pin spacing from	0.197 in
Pin spacing up to	0.2 in
pole count	4
Cross section [mm ²]	0.25 - 0.75 mm ²
Cross section [AWG]	22 - 18 AWG
Wiring method	e
Connection method	PUSH WIRE®
Number of strands	2
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	10 A
Measured voltage EN	500 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	10 A

Weight

4.854 g

Color

gray

Wiring type

Angled Type



No. of connection Points	8
No. of potentials	8
Height	16.5 mm
Height	0.65 in
Width	21.5 mm
Width	0.846 in
Depth	13.5 mm
Depth	0.531 in
Strip length from	10 mm
Strip length to	12 mm
Strip length	0.43 in
xxx-xxx/000-006	blue
xxx-xxx/000-008	dark gray
xxx-xxx/000-009	light gray
xxx-xxx/000-012	orange
xxx-xxx/000-017	light green



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
254-154	ABS	04-HG469925/1-PDA	250	10	2x0,75
254-154	BV	11915/A0	250	10	2x0,75
254-154	CCA	DK96-00648	250	10	2x0,75
254-154	DNV	E-9215	250	16	2x0,75
254-154	GL	17296-00HH	250	10	2x0,75
254-154	KEMA	93.9817.01	250		0,75
254-154	RMR	11130002	250	10	2x0,75
254-154	UR	E45172	300	10	24-18

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected