


Item no.: 254-453
 Product description: 1-CONDUCTOR PCB TERMINAL STRIP 2 SOLDER PINS /
 POLE 3 POLE PIN SPACING 5/5.08 MM / 0.2 IN



Produkt kann von Bild abweichen / product may differ

Packing unit 280 4*70 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Connection method	PUSH WIRE®
Weight	2.342 g
Color	gray
No. of connection Points	3
No. of potentials	3
pole count	3
Height	15.7 mm
Height	0.618 in
Width	16.5 mm
Width	0.65 in
Depth	13.5 mm
Depth	0.531 in
Pin spacing from	5 mm
Pin spacing up to	5.08 mm
Pin spacing from	0.197 in
Pin spacing up to	0.2 in
Pollution degree	2
Measured voltage EN	320 V

Measured shock voltage	4 kV
Current intensity EN	24 A
Pollution degree	2



Measured voltage EN	630 V
Measured shock voltage	4 kV
Current intensity EN	24 A
Cross section [mm ²]	0.5 - 2.5 mm ²
Wiring method	solid
Cross section [mm ²]	0.5 - 1.5 mm ²
Cross section [mm ²]	0.5 - 1.5 mm ²
Cross section [AWG]	20 - 12 AWG
Strip length from	10 mm
Strip length to	12 mm
Material group	I
xxx-xxx/000-006	blue
xxx-xxx/000-008	dark gray
xxx-xxx/000-009	light gray
xxx-xxx/000-012	orange
xxx-xxx/000-017	light green



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
254-453	ABS	04-HG469925/1-PDA	250	10	2,5
254-453	BV	11915/A0	250	10	2,5
254-453	CCA	DK96-00648	250	10	2,5
254-453	CSA	18677-38	300	10	20-12
254-453	DNV	E-9215	250	10	2,5
254-453	GL	17296-00HH	250	10	2,5
254-453	KEMA	93.9817.01	250		2,5
254-453	RMR	11130002	250	10	2,5
254-453	UR	E45172	300	10	20-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected