



PCB TERMINAL STRIP; 2 SOLDER PINS / POLE; 2 POLE; PIN SPACING 5/5.08 MM, 0.2 IN; WITH PUSH BOTTONS; FRONT-ENTRY IL HONGIL HONGIL

Packing unit 400 4*100 pieces

Product group 4 (Printed Circuit)

Pin spacing from 5 mm

Pin spacing up to 5.08 mm

Pin spacing from 0.197 in

Pin spacing up to 0.2 in

pole count 2

Cross section from [mm²] 0.08 mm²

Cross section to [mm²] 2.5 mm²

Cross section from [AWG] 28 AWG

Cross section to [AWG] 12 AWG

Connection method CAGE CLAMP® CONNECTION

Measured voltage EN 250 V

Measured shock voltage 4 kV

Pollution degree 3

Current intensity EN 16 A

Measured voltage EN 500 V

Measured shock voltage 4 kV

Pollution degree 2

Current intensity EN 16 A

Weight 2.47 g

Color gray

Wiring type Front-entry

No. of connection Points 2

No. of potentials 2

Height 14.2 mm

Height 0.559 in

Width 12.9 mm

Width 0.508 in

Depth 18.3 mm

Depth 0.72 in

Strip length from 5 mm

Strip length to 6 mm

Strip length 0.22 in