

Item no.: 256-402  
 Product description: PCB TERMINAL STRIP; 2 SOLDER PINS / POLE; 2 POLE;  
 PIN SPACING 5/5.08 MM / 0.2 IN; FRONT-ENTRY; CAGE  
 CLAMP®CONNECTION



Packing unit 400 4\*100 pieces

Pin spacing from	5 mm
Pin spacing up to	5.08 mm
Pin spacing from	0.197 in
Pin spacing up to	0.2 in
pole count	2
Cross section from [mm <sup>2</sup> ]	0.08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	2.5 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP® CONNECTION
Voltage UL	300 V
Voltage CSA	300/600 V
Current rating UL	15 A
Current rating CSA	15/5 A
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	16 A
Measured voltage EN	500 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	16 A



Color	gray
Wiring type	Angled Type
No. of connection Points	2
No. of potentials	2
Height	18.2 mm
Height	0.72 in
Width	12.9 mm
Width	0.508 in
Depth	17.6 mm
Depth	0.693 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected