

Item no.: 260-152  
 Product description: 2-CONDUCTOR TERMINAL STRIP; LATERAL MARKING; 2 POLE; WITH SNAP-IN MOUNTING FOOT; FOR ALUMINUM RAIL 210-154 OR WITH MOUNTING ADAPTER 209-120 FOR TS 35; SIDE-ENTRY



Packing unit 100 pieces

pole count	2
Cross section from [mm <sup>2</sup> ]	0.08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	1.5 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	16 AWG
Connection method	CAGE CLAMP® CONNECTION
Number of strands	5
Voltage CSA	300 V
Voltage UL	300 V
Current rating UL	10 A
Current rating CSA	15 A
Measured voltage EN	400 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	18 A
Weight	4.2 g
Color	gray
Wiring type	Side-entry
No. of connection Points	4
No. of potentials	2
Height	17 mm
Height	0.669 in



Width	0.567 in
Depth	25 mm
Depth	0.985 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected