

Item no.: 262-180  
 Product description: 2-conductor Ex e II terminal block; LATERAL MARKING; SUITABLE FOR EX E APPLICATIONS; WITH SNAP-IN MOUNTING FOOT; FOR ALUMINUM RAIL 210-154 OR WITH MOUNTING ADAPTER 209-120 FOR TS 35; SIDE-ENTRY



Packing unit 100 pieces

Product group	9 (Std Chassis Mt Blocks)
Cross section from [mm <sup>2</sup> ]	0.5 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	4 mm <sup>2</sup>
Cross section from [AWG]	20 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP® CONNECTION
Measured voltage EN	550 V
Current intensity EN	23 A
Weight	4.21 g
Color	light gray
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	1
Height	23 mm
Height	0.906 in
Width	7 mm
Width	0.276 in
Depth	33.5 mm
Depth	1.32 in
Strip length from	9 mm
Strip length to	10 mm
Strip length	0.37 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
262-180	AEX	E185892	600	20	24-12
262-180	BV	07436/C0			0,08-4
262-180	CCA	NL5802	630		0,08-4
262-180	CCA	TE/1718/880590/08	630		0,08-4
262-180	CSA	18677-45	300/600	20/5	26-12
262-180	cURus-EX	E185892	600	20	24-12
262-180	Dep.MaE	CS4590N	300	34	
262-180	GL	17295-00HH	500	22	4
262-180	GOSENERGO-Ex	99.041	550	23	4
262-180	KEMA	2079569.03	630		0,08-4
262-180	KR	HMB05880-EL002	630	32	4
262-180	NEMKO	L94015	750		4
262-180	PTB	IECEXPTB04.0004U	550	23	4
262-180	PTB	PTB98Atex3125U	550	23	4
262-180	SEMKO	8606200	750		4
262-180	UL	E45172	300/600	20/5	28-12
262-180	UR	E45172	300/600	20/5	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected