

Item no.: 262-311  
 Product description: 2-CONDUCTOR TERMINAL BLOCK; LATERAL MARKING;  
 WITH SNAP-IN MOUNTING FOOT; FOR ALUMINUM RAIL  
 210-154 OR WITH MOUNTING ADAPTER 209-120 FOR TS  
 35; SIDE-ENTRY; CAGE CLAMP® CONNECTION



Packing unit 100 2\*50 pieces

Product group	9 (Std Chassis Mt Blocks)
Cross section from [mm <sup>2</sup> ]	0.08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	4 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP® CONNECTION
Measured voltage EN	630 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	24 A
Weight	4.2 g
Color	gray
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	1
Height	23 mm
Height	0.906 in
Width	7 mm
Width	0.276 in
Depth	33.5 mm
Depth	1.32 in
Strip length from	9 mm
Strip length to	10 mm
Strip length	0.37 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
262-311	ABS	04-HG476174-PDA	630	32	4
262-311	BBJ	B/12/696/03	630	32	4
262-311	BV	07436/C0			0,08-4
262-311	CCA	NL5802	630		0,08-4
262-311	CCA	TE/1718/880590/08	630		0,08-4
262-311	CSA	18677-45	300/600	20/5	26-12
262-311	Dep.MaE	CS4590N	300	34	
262-311	DNV	E7569	630	32	4
262-311	GL	17295-00HH	630	32	4
262-311	KEMA	2079569.03	630		0,08-4
262-311	KR	HMB05880-EL002	630	32	32
262-311	LR	92/20242(E4)	630	24	4
262-311	NEMKO	L94015	500		4
262-311	RMR	11130002	630	32	4
262-311	UL	E45172	300/600	20/5	28-12
262-311	UR	E45172	300/600	20/5	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected