
Item no.: 280-519
Product description: DOUBLE DECK TERMINAL BLOCK; CENTER MARKING;
THROUGH/THROUGH; CARRIER RAIL DIN 35; FRONT-
ENTRY; CAGE CLAMP® CONNECTION



Packing unit 50 pieces

Cross section from [mm ²]	0.08 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	14 AWG
Connection method	CAGE CLAMP® CONNECTION
Voltage UL	300 V
Voltage CSA	300/600 V
Current rating UL	15 A
Current rating CSA	20/5 A
Measured voltage EN	500 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	20 A
Weight	10.057 g
Color	gray
Wiring type	Front-entry
No. of connection Points	4
No. of potentials	2
Height	58.5 mm
Height	2.3 in
Width	5 mm
Width	0.197 in



Depth	2.52 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
280-519	ABS	05-HG476175/1-PDA	500	20	2,5
280-519	BBJ	B/12/700/03	500	20	2,5
280-519	BV	07436/Co	500	20	2,5
280-519	CCA	NL5855	500	20	2,5
280-519	CSA	154112-1536071	300/600	20/5	28-12
280-519	CSM	017956	500	20	2,5
280-519	DEMKO	93117	500		2,5
280-519	Dep.MaE	CS4865N	600	25	2,5
280-519	GL	17295-00HH	500	20	2,5
280-519	KEMA	2082859.07	500	20	2,5
280-519	LR	91/20112(E4)	500	20	2,5
280-519	NEMKO	L86905	500	20	2,5
280-519	PRS	TE/1219/880590/98	500	20	2,5
280-519	RMR	11130002	500	20	2,5
280-519	RosTesT	B09523	500	20	2,5
280-519	UL	E45172	300	15	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected