
Item no.: 280-901
Product description: 2-CONDUCTOR THROUGH TERMINAL BLOCK; CENTER MARKING; CARRIER RAIL DIN 35; FRONT-ENTRY; CAGE CLAMP® CONNECTION; HORIZONTAL TYPE



Packing unit 100 pieces

Cross section from [mm ²]	0.08 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	14 AWG
Connection method	CAGE CLAMP® CONNECTION
Voltage CSA	600 V
Voltage UL	600 V
Current rating UL	20 A
Current rating CSA	25 A
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	24 A
Weight	5.428 g
Color	gray
Wiring type	Front-entry
No. of connection Points	2
No. of potentials	1
Height	28 mm
Height	1.1 in
Width	5 mm
Width	0.197 in



Depth	2.09 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
280-901	ABS	05-HG476175/1-PDA	800	24	2,5
280-901	BBJ	B/12/700/03	800	24	2,5
280-901	BV	07436/Co	800	24	2,5
280-901	CCA	NL5855	800		2,5
280-901	CSA	154112-1536071	600	25	26-12
280-901	CSM	017956	800	24	2,5
280-901	DEMKO	93117-05	750		2,5
280-901	Dep.MaE	CS4865N	600	25	2,5
280-901	DNV	E7570	800	24	2,5
280-901	GL	17295-00HH	800	24	2,5
280-901	KEMA	2082859.07	800		2,5
280-901	KR	HMB05880-EL001	800	26	1,5
280-901	LR	91/20112(E3)	800	24	2,5
280-901	NEMKO	L87053	750		2,5
280-901	PRS	TE/1219/880590/98	800	24	2,5
280-901	RMR	11130002	800	24	2,5
280-901	RosTesT	B09523	800	24	2,5
280-901	UL	E45172	600	20	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected