


Item no.: 281-612
 Product description: Fused disconnect terminal block with pivotable fuse holder for miniature metric fuses 5 x 25 mm without blown fuse indication



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Current intensity EN	10 A
Current intensity EN	6.3 A
Product group	1 (Rail Mounted Terminal Blocks)
for miniature metric fuses	5 x 25 mm
Cross section [mm ²]	0.08 - 4 mm ²
Cross section [AWG]	28 - 12 AWG
Connection method	CAGE CLAMP®CONNECTION
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	10 A
Current intensity EN	6.3 A
Weight	17.32 g
Color	grey
Wiring type	Front-entry
No. of connection Points	2
No. of potentials	2
Height	60 mm
Height	2.36 in

Width
Width
Depth

8 mm
0.315 in
60 mm



Depth	2.36 in
Strip length from	9 mm
Strip length to	10 mm
Strip length	0.37 in
Safety information 1	Nominal voltage and nominal current are defined by the fuse.
Mounting	TS 35



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
281-612	ABS	05-HG476175/3-PDA	800	10	0,08-4
281-612	BV	07436/C0			0,08-4
281-612	CCA	NL5470	800	10	0,08-4
281-612	CSA	154112-1505034	600	10	28-12
281-612	GL	17295-00HH	800	10	4
281-612	KEMA	2036066.01	800	10	4
281-612	PRS	TE/1718/880590/08	800	10	0,08-4
281-612	UR	E45172	600	10	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected