

Item no.: 281-619  
 Product description: DOUBLE DECK TERMINAL BLOCK; CENTER MARKING;  
 THROUGH/THROUGH; CARRIER RAIL DIN 35; FRONT-  
 ENTRY; CAGE CLAMP®CONNECTION



Packing unit 50 pieces

Cross section from [mm <sup>2</sup> ]	0.08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	4 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP® CONNECTION
Voltage CSA	600 V
Voltage UL	600 V
Current rating UL	20 A
Current rating CSA	15 A
Measured voltage EN	500 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	26 A
Weight	14.564 g
Color	gray
Wiring type	Front-entry
No. of connection Points	4
No. of potentials	2
Height	58.5 mm
Height	2.3 in
Width	6 mm
Width	0.236 in



Depth	2.89 in
Strip length from	9 mm
Strip length to	10 mm
Strip length	0.37 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
281-619	ABS	05-HG476175/1-PDA	500	26	4,0
281-619	BBJ	B/12/700/03	500	26	4,0
281-619	BV	07436/Co	500	26	4,0
281-619	CCA	NL5591/1	500	26	4
281-619	CSA	154112-1505034	600	25	28-12
281-619	CSM	017956	500	26	4,0
281-619	DEMKO	75942	750		4
281-619	Dep.MaE	CS4866N	600	25	4
281-619	DNV	E7570	800	10	4,0
281-619	GL	17295-00HH	500	26	4
281-619	KEMA	2076376.01	500	26	4
281-619	KR	HMB05880-EL001	500/800	10/35	4
281-619	LR	91/20112(E3)	500	26	4,0
281-619	PRS	TE/1219/880590/98	500	26	4,0
281-619	RMR	11130002	500	26	4,0
281-619	RosTesT	B09523	500	26	4,0
281-619	UL	E45172	600	20	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected