


Item no.: 745-354
Product description: PCB TERMINAL STRIP 2 SOLDER PINS / POLE 4 POLE PIN
SPACING 10 MM / 0.394 IN WITHOUT FIXING FLANGE



Produkt kann von Bild abweichen / product may differ

Packing unit 48 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	10.998 g
Color	gray
No. of connection Points	4
No. of potentials	4
pole count	4
Height	23 mm
Height	0.906 in
Width	39.1 mm
Width	1.539 in
Depth	29.1 mm
Depth	1.15 in
Pin spacing from	10 mm
Pin spacing from	0.394 in
Pollution degree	2
Measured voltage EN	1000 V
Measured shock voltage	8 kV
Current intensity EN	41 A
Pollution degree	2

Measured voltage EN	1000 V
Measured shock voltage	8 kV
Current intensity EN	41 A



Connection method	CAGE CLAMP® CONNECTION
Cross section [mm²]	0.2 - 6 mm²
Wiring method	solid
Cross section [mm²]	0.2 - 6 mm²
Cross section [mm²]	0.25 - 4 mm²
Cross section [mm²]	0.25 - 4 mm²
Cross section [AWG]	24 - 10 AWG
Strip length from	11 mm
Strip length to	12 mm
Material group	I
xxx-xxx/000-006	blue
xxx-xxx/000-009	light gray
xxx-xxx/000-016	green-yellow
xxx-xxx/000-017	light green
xxx-xxx/005-000	with fixing flange
xxx-xxx/005-xxx	with fixing flange



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
745-354	CCA	NL6296	630	41	0,02-6
745-354	cURus	E45172	300	30	24-10
745-354	KEMA	2076500.02	630	41	0,02-6
745-354	KEMA	2097989.01	630	41	0,02-6

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected