


Item no.: 750-600  
Product description: END MODULE CAGE CLAMP®CONNECTION



Packing unit 1 piece



Product group	15 (I/O System)
Operating temperature	0 °C ... + 55 °C
Storage temperature	-25 °C ... +85 °C
Relative air humidity	95 %
Vibration resistance	acc. IEC 60068-2-6
Shock resistance	acc. IEC 60068-2-27
Degree of protection	IP 20
EMC immunity to interference	acc. EN 50082-2 (96)
EMC emission of interference	per EN 50081-1 (93)
EMC marine applications - noise proof	gem. Germanischer Lloyd (2003)
EMC marine applications - noise transmission	gem. Germanischer Lloyd (2003)
Conformity marking	CE
Approvals	ATEX
Weight	33.5 g
Color	light gray
Height	64 mm
Height	2.52 in
Width	12 mm
Width	0.472 in
Depth	100 mm
Depth	3.937 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
750-600	ABS	03-HG374860/2-PDA			
750-600	ABS	ES 578983-X			
750-600	BSH	Bescheinigung Nr. 467			
750-600	BV	13453/B0 BV			
750-600	DNV	A-10191			
750-600	GL	26 898 - 05 HH			
750-600	IECEX	IECEX PTB 07.0064X			
750-600	KEMA	01 ATEX 1024 X			
750-600	KR	HMB05880-EL004			
750-600	KR	HMB05880-EL005			
750-600	LR	02/20026 (E2)			
750-600	NK	TA06190M			
750-600	PRS	TE/1720/880590/08			
750-600	Rina	ELE153207CS001			
750-600	UL	E175199 Sec.1			
750-600	UL	E198726 Sec.1			
750-600	UL DEMKO A/S	DEMKO 08 ATEX 142851 X			

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected