

Item no.: 769-109/022-000
 Product description: 1-CONDUCTOR ANGLED FEMALE PLUG FOR USE WITH RECEPTACLE TERMINAL BLOCKS OF SERIES 769 AND 870 OR MALE CONNECTORS 9 POLE WITH CODING FINGERS



Packing unit 50 pieces

| | |
|----------------------------------|--------------------------|
| Product group | 18 (X-COM-SYSTEM) |
| pole count | 9 |
| Cross section [mm ²] | 0.08 - 4 mm ² |
| Cross section [AWG] | 28 - 12 AWG |
| Connection method | CAGE CLAMP® CONNECTION |
| Measured voltage EN | 500 V |
| Measured shock voltage | 6 kV |
| Pollution degree | 3 |
| Current intensity EN | 32 A |
| Weight | 23.82 g |
| Color | gray |
| Wiring type | Angled Type |
| No. of connection Points | 9 |
| No. of potentials | 9 |
| Height | 37.1 mm |
| Height | 1.461 in |
| Width | 45 mm |
| Width | 1.799 in |
| Depth | 26.5 mm |
| Depth | 1.043 in |
| Strip length from | 8 mm |
| Strip length to | 9 mm |
| Strip length | 0.33 in |



| Item no. | Admission office | Approval no. | Voltage [V] | Current [A] | Cross section [mm ²] |
|-----------------|------------------|-----------------|-------------|-------------|-----------------------------------|
| 769-109/022-000 | ABS | 04-HG476175-PDA | 500 | 32 | 4 |
| 769-109/022-000 | CSA | 154112-1101144 | 300/300/600 | 20/20/5 | 28-12 |
| 769-109/022-000 | KEMA | 2077750.01 | 500 | 32 | 4 |
| 769-109/022-000 | UR | E45171 | 600 | 20 | 16-12 |
| 769-109/022-000 | UR | E45172 | 300/300/600 | 20/20/5 | 28-12 |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected