


Item no.: 769-603
 Product description: Plug WITH CAGE CLAMP®CONNECTION FOR FREE CONNECTION PIN SPACING 5 MM / 0.197 IN 3 POLE



Produkt kann von Bild abweichen / product may differ

Packing unit 100 pieces

RoHS compliant

Product group	18 (X-COM-SYSTEM)
Pin spacing from	5 mm
Pin spacing from	0.197 in
pole count	3
Cross section [mm ²]	0.08 - 4 mm ²
Cross section [AWG]	28 - 12 AWG
Measured voltage EN	500 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	32 A
Weight	9.43 g
Color	gray
Wiring type	Front-entry
No. of connection Points	3
No. of potentials	3
Height	18.3 mm
Height	0.72 in
Width	18.6 mm
Width	1.732 in

Depth	40.2 mm
Depth	1.583 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
769-603	ABS	05-HG476175/3-PDA	500	32	4
769-603	CSA	154112-1101144	300	20	28-12
769-603	KEMA	2077750.01	500	32	4
769-603	UR	E45171	600	20	16-12
769-603	UR	E45172	300	20	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected