

Item no.: 770-223  
 Product description: SOCKET; WITHOUT RELIEF HOUSING; 3 POLE; PIN SPACING 10 MM / 0.394 IN; 100% PROTECTED AGAINST MISMATING; CAGE CLAMP®S CONNECTION



Packing unit 100 pieces  
 RoHS compliant

Product group	20 (WINSTA)
pole count	3
Cross section from [mm <sup>2</sup> ]	0,5 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	4 mm <sup>2</sup>
Cross section from [AWG]	20 AWG
Cross section to [AWG]	12 AWG
Connection method	CONTACT CAGE CLAMP®CONNECTION
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	25 A
Weight	9,504 g
Color	white
No. of connection Points	6
No. of potentials	3
Height	12,9 mm
Height	0,508 in
Width	30 mm
Width	1,181 in
Depth	37,5 mm
Depth	1,476 in
Strip length from	9 mm
Strip length to	9 mm
Strip length	0,35 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
770-223	CBCertificateVDE	DE1-29543	250/400	25	0,5-4
770-223	CCA	NL5566	250	25	0,5-4,0
770-223	cURus	E45171	600	20	12
770-223	DNV	E6188	250	25	4
770-223	GL	42875-02HH	250	25	4
770-223	KEMA	2060958.01	250	25	0,5-4,0
770-223	LR	02/20050(E1)	250	25	2,5
770-223	LR	02/20050(E3)	250	25	2,5
770-223	PRS	TE/1719/880590/08	250	25	0,5-4,0

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected