
Item no.: 773-514
Product description: PUSH-WIRE CONNECTOR FOR JUNCTION BOXES; 4-
CONDUCTOR TERMINAL BLOCK; PUSH-WIRE
CONNECTION



Packing unit 500 10*50 pieces

Product group	7 (Push Wire Conn.)
Continuous operating temperature	150 °C
Cross section from [mm ²]	0.75 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	18 AWG
Cross section to [AWG]	12 AWG
Wiring method	e
Connection method	PUSH-WIRE CONNECTION
Number of strands	4
Cross section from [mm ²]	1.5 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	16 AWG
Cross section to [AWG]	12 AWG
Wiring method	e
Connection method	PUSH-WIRE CONNECTION
Number of strands	4
Measured voltage EN	400 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	24 A
Weight	2.539 g
Color	black



No. of connection Points	4
No. of potentials	1
pole count	4
Height	13.1 mm
Height	0.516 in
Width	13 mm
Width	0.512 in
Depth	19.5 mm
Depth	0.768 in
Strip length from	12 mm
Strip length to	12 mm
Strip length	0.47 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
773-514	UL	E69654	600	20	12-18

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected