

Item no.: 273-103
 Product description: PUSH-WIRE CONNECTOR FOR JUNCTION BOXES; 8-
 CONDUCTOR TERMINAL BLOCK; PUSH-WIRE
 CONNECTION



Packing unit 500 10*50 pieces

Product group	7 (Push Wire Conn.)
pole count	8
Cross section from [mm ²]	1 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	14 AWG
Cross section to [AWG]	12 AWG
Wiring method	e
Connection method	PUSH-WIRE CONNECTION
Number of strands	8
Measured voltage EN	400 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	24 A
Weight	4.67 g
Color	dark gray
Wiring type	Side-entry
No. of connection Points	8
No. of potentials	1
Height	17 mm
Height	0.669 in
Width	17.5 mm
Width	0.689 in



Depth	0.768 in
Strip length from	10 mm
Strip length to	13 mm
Strip length	0.45 in

Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
273-103	ABS	04-HG476172-PDA	400	24	2,5
273-103	ASTA	Cert.No.167	400	24	0,75-2,5
273-103	BBJ	B/12/694/03	400	24	2,5
273-103	BV	11914/AO	400	24	2,5
273-103	CCA	DK2515	400	24	2,5
273-103	CSA	154112-1059435	600	10	20-16
273-103	CSM	017956	400	24	2,5
273-103	DEMKO	40677-02	400	24	2,5
273-103	DEMKO	99-00683	400	24	2,5
273-103	Dep.MaE	CS4573N	300		8x(0,75-2,5)
273-103	DNV	E7569	400	24	2,5
273-103	FIMKO	FI13213	400	24	2,5
273-103	GL	17294-00HH	400	24	2,5
273-103	KEMA	97.1394.01	400	18	0,75-2,5
273-103	LCIE	273898	380		2,5
273-103	LR	04/20013(E1)	400	24	2,5
273-103	NEMKO	99101318	400	24	2,5
273-103	ÖVE	1193-033-01	400	24	2,5
273-103	RosTesT	B09523	400	24	2,5
273-103	SEMKO	9921002/01-03	400	24	2,5
273-103	SEV	99,770286,01	400	24	2,5
273-103	UL	E69654	600	20	16-14
273-103	VDE	123899	400	24	2,5

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected