

NT90 (T90)



30.5 × 24.2 × 17

32.5 × 27.6 × 20.5

CQC 03001003503

UL US E160644

R2033977

Patent No.: 95213824.7 99218304.9

99312549.2 01311661.4 02110881.1

Features

- Small size, light weight. Low coil power consumption, heavy contact load.
- reliability, long life. Strong anti-shock and anti-vibration, high
- PC board mounting.
- Suitable for automobile, machine, electronic equipment, air conditioner and household appliances applications.

Ordering Information

NT90 R H A S DC12V CB 0.9

1 2 3 4 5 6 7 8 9

- | | |
|---|---|
| 1 Part number: NT90(T90) | 6 Coil rated voltage(V): AC:12,24,110,120,220 |
| 2 Terminal: R: without Pin6: NIL: With Pin6 | DC:3,5,6,9,12,15,18,24,48,110 |
| 3 Load: H:30A; N:40A | 7 Contact material: C: AgCdO ; S: AgSnO ₂ |
| 4 Contact arrangement: 1A:1A; 1B:1B; 1C:1C | 8 Resist heat class: B:130℃ F:155℃ |
| 5 Enclosure: S: Sealed type; D: Dust cover; E: Covered O: Open type | 9 Coil power consumption: 0.6:0.6W; 0.9:0.9W
NIL:2VA |

Contact Data

Contact Arrangement	1A SPSTNO 1B(SPSTNC) 1C(SPDT(B-M))
Contact Material	AgCdO 2 AgSnO
Contact Rating (resistive)	NO:30A/240VAC,14VDC; NC:20A/240VAC;30A/14VDC NO:40A/240VAC,30VDC; NC:30A/240V AC,30VDC (0.9W) NO:30A/277VAC;NC:20A/277V AC
	Motor load : 2HP 250VAC : 1.5HP 250V Lamp load : TV-5
Max. Switching Power	1100W 7200VA
Max. Switching Voltage	10VDC 250VAC Max. Switching Current:40A
Contact Resistance or Voltage drop	≤ 30mΩ Item 4.12 of IEC 61810-7
Operation life	Electrical 10 Item 4.30 of IEC 61810-7
	Mechanical 10 Item 4.31 of IEC 61810-7

Coil Parameter

Dash numbers	Rated voltage VAC		Rated current mA	Coil resistance Ω ±10%	Pick up voltage VAC(max) (75%of rated voltage)	Release voltage VAC(min) (30%of rated voltage)	Coil power	Operate Time ms	Release Time ms
	Rated	Max							
012AC	12	15.6	187	27	9.0	3.6	2VA	—	—
024AC	24	31.2	95	120	18.0	7.2			
110AC	110	143	20	2360	82.5	33.0			
120AC	120	156	16.5	3040	90.0	36.0			
220AC	220	286	6.4	13490	165.0	66.0			

CAUTION: 1.The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.
2.Pickup and release voltage are for test purposes only and are not to be used as design criteria.

NT90(T90)

Coil Parameter

DC Coil Parameter								
Dash numbers	Rated voltage V		Coil resistance $\Omega \pm 10\%$	Pick up voltage V(max) (75% of rated voltage)	Release voltage V(min) (10% of rated voltage)	Coil power W	Operate Time ms	Release Time ms
	Rated	Max						
003-900	3	3.9	10	2.25	0.3	0.9	<15	<10
005-900	5	6.5	28	3.75	0.5			
006-900	6	7.8	40	4.50	0.6			
009-900	9	11.7	90	6.75	0.9			
012-900	12	15.6	160	9.00	1.2			
015-900	15	19.5	250	10.25	1.5			
018-900	18	23.4	360	13.50	1.8			
024-900	24	31.2	640	18.00	2.4			
048-900	48	62.4	2560	36.00	4.8			
110-900	110	143	13445	82.50	11.0			
003-600	3	3.9	15	2.25	0.3	0.6	<15	<10
005-600	5	6.5	42	3.75	0.5			
006-600	6	7.8	60	4.50	0.6			
009-600	9	11.7	135	6.75	0.9			
012-600	12	15.6	240	9.00	1.2			
015-600	15	19.5	375	10.25	1.5			
018-600	18	23.4	540	13.50	1.8			
024-600	24	31.2	960	18.00	2.4			
048-600	48	62.4	3840	36.00	4.8			
110-600	110	143	20167	82.50	11.0			

- CAUTION:** 1.The use of any coil voltage less than the rated coil voltage will compromise the operation of the relay.
 2.Pickup and release voltage are for test purposes only and are not to be used as design criteria.

Operation condition

Insulation Resistance	1000M Ω min (at 500VDC)	Item 7 of IEC255-5
Dielectric Strength	50Hz 1500V	Item 6 of IEC255-5
Between contacts	50Hz 2500V 4000V (without Pin 6)	Item 6 of IEC255-5
Between contact and coil		
Shock resistance	200m/s ² 11ms	IEC68-2-27 Test Ea
Vibration resistance	10~55Hz double amplitude 1.5mm	IEC68-2-6 Test Fc
Terminals strength	10N	IEC68-2-21 Test Ua1
Solderability	235 \pm 2 $^{\circ}$ C 3 \pm 0.5s	IEC68-2-20 Test Ta method 1
Ambient Temperature	-55~100 $^{\circ}$ C -55~125 $^{\circ}$ C	
Relative Humidity	85% (at 40 $^{\circ}$ C)	IEC68-2-3 Test Ca
Mass	27g (Open type) 30g	

Qualification inspection:



Perform the qualification test as specified in the table IV of IEC255-19-1 and minimum sample size 24.

Safety approvals


Safety approval	UL&CUR	UL T	CQC
Load	NO:40A/240VAC 30A/277V NC:30A/240VAC 20A/277V 2 HP 250VACV-5 $\frac{1}{2}$ HP 250VAC HP:A 1HP/16AFLA/120V AC 2HP/12AFLA/240VAC B 30LRA/10AFLA/120VAC 30LRA/10AFLA/240VAC Insulation class F-class	NO:40A/240VAC 14VDC NC:30A/240VAC 14VDC Insulation class F-class	NO:30A/240VAC NC:20A/240VAC

Dimensions

mm /inch




Open type



Wiring diagram(Bottom view)

Dimensions



Mounting (Bottom view)

- NOTES 1).Dimensions are in millimeters.
 2).Inch equivalents are given for general information only

Reference Data

