

---

Item no.: 280-681  
Product description: 3-CONDUCTOR THROUGH TERMINAL BLOCK; CENTER MARKING; FRONT-ENTRY; CAGE CLAMP® CONNECTION; HORIZONTAL TYPE

---



Packing unit 100 pieces

Product group	1 (Rail Mounted Terminal Blocks)
Cross section from [mm <sup>2</sup> ]	0.08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	2.5 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Connection method	CAGE CLAMP® CONNECTION
Voltage UL	600 V
Voltage CSA	600 V
Current rating UL	20 A
Current rating CSA	25 A
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	24 A
Weight	7.66 g
Color	gray
Wiring type	Front-entry
No. of connection Points	3
No. of potentials	1
Height	28 mm
Height	1.1 in
Width	5 mm



Depth	64 mm
Depth	2.52 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
280-681	ABS	05-HG476175/1-PDA	800	24	2,5
280-681	BBJ	B/12/700/03	800	24	2,5
280-681	BV	07436/Co	800	24	2,5
280-681	CCA	NL5855	800		2,5
280-681	CSA	154112-1536071	600	15	28-12
280-681	CSM	017956	800	24	2,5
280-681	DEMKO	78571	750		2,5
280-681	Dep.MaE	CS4865N	600	25	2,5
280-681	DNV	E7570	800	20	2,5
280-681	GL	17295-00HH	800	24	2,5
280-681	KEMA	2082859.07	800		2,5
280-681	LR	91/20112(E4)	800	24	2,5
280-681	PRS	TE/1219/880590/98	800	24	2,5
280-681	RMR	11130002	800	24	2,5
280-681	RosTesT	B09523	800	24	2,5
280-681	UL	E45172	600	20	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected